

Tubular Leverset



T621 series Leverset on round rose



SPECIFICATIONS

Exposed Trim: Zinc Alloy lever trim could be plated to match finishes indicated.
 Keying: 5-pins tumbler SCH-C keyway with three brass nickle plated keys. Various keyways selectable.
 Door Range: 1-3/8" to 1-3/4" (35mm to 55mm) standard.
 Backset: Adjustable 2-3/8"(60mm) and 2-3/4"(70mm) backset.

STANDARD FEATURES

- Wrought steel tubular lock housing with chromated finish for better corrosion resistance.
- Completely left hand and right hand door reversible.
- Three-piece assembly for fast easy installation.
- Meets 200,000 cycles ANSI A156.2 Grade 3 requirements.

FUNCTION

00		Entrance
10		Privacy
30		Passage
50		Storeroom

- ※ Double torsion spring available for smooth operation
- ※ Spool pins available for anti-picking feature.
- ※ Bottom loaded cylinder house for easy rekeying.
- ※ Anti-pry shield available.

FINISHES

CODE	AB	AC	PB	SB	ORB	PVD
BHMA	609	616	605	606	613	505
US	5	11	3	4	10B	11P



CODE	SS	PS	CP	SC	AN	SN
BHMA	630	632	625	626	620	619
US	32D	32	26	26D	15A	15



MARCO POLO ARCHITECTURAL HARDWARE