Tubular Leverset





T627 series Leverset on round rose

SPECIFICATIONS

Exposed Trim: Zinc Alloy lever trim could be plated to match finishes indicated.

Keying: 5-pins tumbler SCH-C keyway with three brass nickle plated keys. Various keyways selectable.

Door Range: 1-3/8" to 1-3/4" (35mm to 55mm) standard.

Backset: Adjustable 2-3/8"(60mm) and 2-3/4"(70mm) backset.

STANDARD FEATURES

- ■Wrought steel tubular lock housing with chromated finish for better corrosion resistance.
- ■Completely left hand and right hand door reversible.
- ■Three-piece assembly for fast easy installation.
- ■Meets 200,000 cycles ANSI A156.2 Grade 3 requirements.

FUNCTION 00 Entrance 10 Privacy 30 Passage 50 Storeroom

- * Double torsion spring available for smooth operation
- X Spool pins available for anti-picking feature.
- Bottom loaded cylinder house for easy rekeying.
- **X** Anti-pry shield available.

INISHES						
CODE	AB	AC	PB	SB	ORB	PVD
BHMA	609	616	605	606	613	505
US	5	11	3	4	10B	11P
			0			
CODE	SS	PS	CP	SC	AN	SN
BHMA	630	632	625	626	620	619
US	32D	32	26	26D	15A	15
		0	0	9		

MARCO POLO ARCHITECTURAL HARDWARE