

HEAVY DUTY TUBULAR LEVER SET



T904 series LEVER SET



SPECIFICATIONS

Exposed Trim: Zinc alloy handle trim to be plated to match finishes indicated.

Keying: 5-pins tumbler SCH-C keyway with three brass nickel plated keys. Various keyways selectable.

Door Range: 1-3/8" to 1-3/4" (35mm to 52mm) standard.

Backset: 2-3/8"(60mm) or 2-3/4"(70mm) backset.

STANDARD FEATURES

- Wrought steel tubular lock housing with chromated finish for better corrosion resistance.
- Completely left hand and right hand door reversible.
- Three-piece assembly for fast easy installation.
- Meets 200,000 cycles ANSI A156.2 Grade 2 requirements.

FUNCTION

00		Entrance Latchbolt operated by lever from either side. Outside lever locked by push button from inside. Unlocked by key from outside or rotating inside lever. When outside lever locked by push and turn button from inside, key from outside or rotating inside lever retracts latch, does not unlock outside lever.
80		Classroom Latchbolt operated by knob from each side. Outside knob locked or unlocked by key from outside. Inside knob always operates latch
50		Storeroom Latch operated by rotating inside lever or key in outside lever. Outside lever always fixed
10		Privacy Latchbolt operated by lever from either side. Outside lever locked by push button on inside. Unlocked by emergency release on outside, rotating inside lever, or closing door
30		Passage Latchbolt operated by lever from either side at all times

1. Two piece knob for better security.
2. Double torsion spring available for smooth operation
3. Spool pins available for anti-picking feature.
4. Bottom loaded cylinder house for easy rekeying.
5. Anti-pry shield available.



T905

FINISHES

CODE	AB	AC	PB	SB	ORB	PVD
BHMA	609	616	605	606	613	505
US	5	11	3	4	10B	11P



CODE	SS	PS	CP	SC	AN	SN
BHMA	630	632	625	626	620	619
US	32D	32	26	26D	15A	15



MARCO POLO ARCHITECTURAL HARDWARE